

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Original) An electrode of an electrochemical battery comprising:  
an electrode catalyst; and  
an electrode catalyst support member made of a fiber stack of conductive metal material to which the electrode catalyst is attached.
2. (Original) The electrode of claim 1, wherein the electrode catalyst has a granule form.
3. (Original) The electrode of claim 1, wherein the electrode catalyst has a filament shape.
4. (Currently Amended) The electrode of ~~one of claims 1 to 3~~ claim 1, wherein the surface of the electrode catalyst is coated with nickel.
5. (Original) The electrode of claim 4, wherein the electrode catalyst support member is made of nickel or a nickel alloy.

6. (Original) The electrode of claim 1, wherein the electrode catalyst support member is a fiber sintered body formed by sintering fibers of conductive metal material.

7. (Original) The electrode of claim 1, wherein the electrode catalyst support member is formed with a pair of sheets with an electrode catalyst attached only at one side thereof, and the pair of sheets are mutually overlapped in such a manner that the sides with the electrode catalyst attached thereon meet.

8. (Original) The electrode of claim 1, further comprising:  
a housing for accommodating the electrode catalyst support member, being made of metal material with a conductivity, and having a plurality of holes.

9. (Original) The electrode of claim 8, wherein the housing is a mesh.

10. (Currently Amended) The electrode of claim 8[[ or 9]], wherein the housing is made of nickel or nickel alloy.

11. (Original) The electrode of claim 1, wherein the electrode catalyst support member additionally contains fluoro polymer.

12. (Original) The electrode of claim 11, wherein the fluoro polymer is PTFE.
13. (Original) The electrode of claim 1, wherein the fiber of the electrode catalyst support member has a diameter of  $1 \sim 100 \mu\text{m}$ .
14. (Currently Amended) The electrode of claim 1 [[or 13]], wherein the fiber constituting the electrode catalyst support member has a length of  $10 \sim 10,000 \mu\text{m}$ .
15. (Original) The electrode of claim 1, wherein the electrode catalyst is metal halide.
16. (Original) The electrode of claim 1, wherein the electrode catalyst is hydrogen storage alloy.
17. (Original) An electrochemical battery having the electrode of claim 1.
18. (Original) The battery of claim 17, wherein the electrochemical battery is a fuel cell.
19. (Original) An electrode of an electrochemical battery made of a fiber stack of an electrode catalyst.

20. (Original) A method for manufacturing an electrode of an electrochemical battery comprising the steps of:

attaching an electrode catalyst to an electrode catalyst support member made of a fiber stack of conductive metal material; and

forming the electrode catalyst support member with the electrode catalyst attached thereto as an electrode of an electrochemical battery.

21. (Original) The method of claim 20, wherein the electrode catalyst has a granule form.

22. (Original) The method of claim 20, wherein, in the attaching step, the electrode catalyst support member is put in a solution, and the electrode catalyst is dispersed on the electrode catalyst support member, so as to be attached thereto.

23. (Original) The method of claim 22, wherein, in the attaching step, liquid particles containing the granule type electrode catalyst are sprayed to the electrode catalyst support member, so as to be attached thereto.

24. (Currently Amended) The method of claim [[22 or]] 23, wherein the attaching step comprises a sub-step of drying the electrode catalyst support member after the liquid particles are sprayed.

25. (Original) The method of claim 20, wherein the electrode catalyst support member is a metal fiber sintered body formed by sintering fibers of conductive metal material.

26. (Original) The method of claim 20, wherein the forming step comprises:  
press-molding the electrode catalyst support member with the electrode catalyst attached thereto; and  
processing the press-molded electrode catalyst support member to an electrode in a desired size.

27. (Currently Amended) The method of claim 26, wherein, in the press-molding step, [[the]] a pair of electrode catalyst support [[member]] members with the electrode catalyst attached thereto [[is]] are press-molded by mutually overlapping the sides with the electrode catalyst attached thereto.

28. (Currently Amended) The method of claim 26 [[or 27]], further comprising the step of:

enclosing the processed electrode with a housing which is made of metal material with a conductivity and has a plurality of holes, after the processing step.

29. (Original) The method of claim 28, wherein the housing is made of nickel or a nickel alloy.

30. (Currently Amended) The method of claim 28 [[or 29]], wherein the housing is a mesh.

31. (Original) The method of claim 20, wherein the electrode catalyst support member is a non-woven fabric made of conductive metal material.

32. (Original) The method of claim 20, wherein the electrode catalyst has a filament shape.

33. (Original) The method of claim 20, wherein the electrode catalyst is metal halide.